U. S. Steel Corporation Clairton Works:
Blast Furnace Blowing Engine Building
400 State Street
Clairton
Allegheny County
Pennsylvania

HAER No. PA-49A

MACO PA 2-CHAIR IA

## PHOTOGRAPHS

HISTORICAL AND DESCRIPTIVE DATA

Historic American Engineering Record National Park Service Department of the Interior Washington, D. C. 20240

## 2 - CLAIR

## HISTORIC AMERICAN ENCINEERING RECORD

U. S. STEEL CORPORATION CLAIRTON WORKS: BLAST FURNACE BLOWING ENGINE BUILDING

HAER No. PA-49A

Location:

400 State Street

Clairton, Allegheny County, Pennsylvania

UTM: 17.595740.4460150

Quad: McKeesport, Pennsylvania

Date of Construction:

1903

Builder/Designer:

Southwark Foundry & Machine Company

Pittsburgh, Pennsylvania

Present Use:

Not in use

Significance:

This building houses seven vertical cross-compound condensing steam engines. These blowing engines originally produced wind for the Clairton Works blast furnaces. In ca. 1961, two furnaces (#6 and

#7) were torn down.

Specifications:

Type: Cross-compound Steeple Condensing

Bore & Stroke: 48x84x84x60

RPM: 40 (60 max) PSI: 140-150 SAT

Valves: HP, Corliss; LP, Corliss Double Ported Connect. Rod & Ends: 12'6" wedge adjustment

Const. of Crank: Porter type

Flywheel Dia. & Face: 20 feet; rim section 418.5"2

Flywheel Type & Const.: Sectional C. I 98.700#

Governor: Flyball Bearings: 2.22"x40"

Design Function: Make wind for blast furnaces Boiler Type/Setting/Fuel: orig. 40 300 WP B&W

boilers with blast fce. gas

Weight: 800,000 1bs.

Cost: \$45,000

Air Pressure: 16-1/2 psi average; 30 psi max. Inlet valve - Cridiron positive Area: 732 in<sup>2</sup> Outlet valve - Gridiron automatic: Area: 528 in<sup>2</sup>

Capacity: 770 ft<sup>3</sup> free air/rev. Diameter Discharge pipe: 30" Steam Pipe diameter: 15" HP Exhaust Pipe diameter: 15"

Receiver: 38"x19'0"

LP Exhaust Pipe diameter: 26"

U. S. Steel Corporation Clairton Works Blast Furnace Blowing Engine Bldg. HAER No. PA-49A (Page 2)

## Condenser No. 1

Type: Weiss Counter Current
Capacity: 15,000 HP
140,000 lbs. steam/hr. condensed
Size steam inlet: 42"x72"

Size steam inlet: 42"x72" Size water inlet: 30" Water required/hr: 420,000

Source water supply: Blast furnace cooling plates

Average vaccuum: 24"

Also served power engines, river pumps (none of which remain)

Box bed: 14', 9" x 9'1"; two per engine

Prepared for transmittal by: Jean P. Yearby, 1984, from data compiled by Field Curry, 1975